

### WarmMark® Temperature Indicators

WarmMark temperature indicators alert users of exposure to unacceptably high temperature conditions and the cumulative amount of time above the temperature threshold. Without them, a cold chain breach may go unnoticed resulting in a compromise in your product's quality.

# How can you be sure that unacceptable temperature during transit has not compromised your product's quality and efficacy?

Refrigeration equipment is not always reliable. Temperatures can vary dramatically during transit – trailer, distribution centers, storage. Your product may encounter unexpected delays in areas with less than ideal conditions.

WarmMark time-temperature indicators provide a cost-effective tool for monitoring the temperature of your package. They are single-use devices that provide accurate, irreversible evidence of a temperature excursion. With the information you gather from these indicators, you can make smarter decisions across your cold chain.





#### **Benefits**

- Delivers irreversible evidence of exposure to unacceptable temperature conditions
- Provides cost-effective solution for last mile monitoring
- Enables easy accept/reject decisions to be made
- Assists in verifying the adequacy of the cold chain packaging
- Aids in compliance with regulatory guidelines
- Saves money and space since field armable indicators require no special packaging or storage



Duo www.warmmark.com





## WarmMark® Temperature Indicators

### **WarmMark Key Specifications**

| Temperature Accuracy | ± 1°C / ± 2°F  |
|----------------------|--|
| Storage Conditions   | Store below the response temperature and below 55% relative humidity for optimal shelf life. |
| Shelf Life           | 2 years from date of sale  |

### **Available Temperature** Run Out Times\*

| 3 Window Indicators                                     | Brief      | Moderate | Prolonged |
|---|------------|----------|-----------|
| -18°C / 0°F   | 1 hr       | 3 hrs    | 12 hrs    |
| 0°C / 32°F<br>8°C / 46°F<br>10°C / 50°F<br>20°C / 68°F  | 2 hours    | 12 hours | 48 hours  |
| 5°C / 41°F<br>25°C / 77°F<br>30°C / 86°F<br>37°C / 99°F | 30 minutes | 2 hours  | 8 hours   |

| Single Window Indicators |        |  |  |
|--------------------------|--------|--|--|
| 8°C / 46°F               | 8 hrs  |  |  |
| 8°C / 46°F               | 12 hrs |  |  |
| 25°C / 77°F              | 8 hrs  |  |  |

| <b>Duo Indicator</b> | Window 1 | Window 2 | Window 3 | Window 4          |
|----------------------|----------|----------|----------|-------------------|
| 10°C / 50°F          | 3 days   | 8 days   | 14 days  |                   |
| 34°C /93°F           |          |          |          | Within 30 minutes |

| <b>Long Run Indicators</b> | Line 1   | Line 2   | Line 3   | Line 4    | Line 5    |
|----------------------------|----------|----------|----------|-----------|-----------|
| 10°C / 50°F                | 12 hours | 30 hours | 60 hours | 110 hours | 168 hours |
| 31°C /88°F                 | 12 hours | 30 hours | 60 hours | 110 hours | 168 hours |

#### WarmMark Use Instructions

- 1. All WarmMark breach window(s) should be white prior to arming the device.
- 2. Before arming, the WarmMark indicator should be placed in an environment at least 5°C (9°F) below the WarmMark's activation threshold temperature for a minimum of 30 minutes.
- 3. To arm the WarmMark indicator, fold up and pull out the indicator's activation tab until the tab and barrier film have been completely removed.
- 4. If using a WarmMark indicator with a threshold temperature below the ambient temperature, immediately place the indicator in the environment to be monitored to avoid early activation.
- 5. Remove the adhesive liner from the WarmMark and adhere the indicator to a clean, dry surface.
  - a. The WarmMark should be located where it will be visible to the receiver of the monitored shipment.
  - b. The WarmMark can be adhered directly to the product being monitored or located inside the packaging.
  - \*Run out times are based on a constant temperature 2°C above the indicator threshold. Exposure to higher temperatures will result in faster run out.



SHOCKWATCH®

www.spotsee.io Rev: 03/2018